

# House Detail Cross Section

Roof Framing: Check  
 \_\_\_ Dimensional \_\_\_/12 Pitch  
 \_\_\_ Engineered Truss : \_\_\_/12 Pitch  
 Spacing: \_\_\_ o.c.

Attic Insulation Type:  
 Fill Depth  
 \_\_\_ "

Roof:  
 Sheathing thickness \_\_\_"  
 \_\_\_ lb Underlayment  
 \_\_\_ Ice and Water Shield  
 Roofing Type: \_\_\_\_\_

Drip Edge Type: \_\_\_\_\_  
 Fascia Type: \_\_\_\_\_

\_\_\_ " Fire Separation Finish

Ceiling Height \_\_\_ "

Tie Plate  
 Wall Plate  
 Insulation Type: \_\_\_\_\_  
 Stud Size \_\_\_"X\_\_\_"  
 Spacing: \_\_\_ o.c.

Vented Soffit Type: \_\_\_\_\_

\_\_\_ " Subfloor  
 Type \_\_\_\_\_

Floor Joist: Type: \_\_\_\_\_  
 Size: \_\_\_\_\_  
 Spacing: \_\_\_ " o.c.

Insulation

Rim Joist: Type: \_\_\_\_\_  
 Size: \_\_\_\_\_

Wall Finish \_\_\_ "

Siding Type: \_\_\_\_\_

Vapor Barrier

House Wrap Type: \_\_\_\_\_

Ceiling Height: \_\_\_ "

Wall Sheathing:  
 Type: \_\_\_\_\_  
 Thickness: \_\_\_ "

Subfloor: Thickness: \_\_\_ "

Floor Joist Type: \_\_\_\_\_  
 Size: \_\_\_\_\_  
 Spacing \_\_\_ " o.c.

Rim Joist: Type: \_\_\_\_\_  
 Size: \_\_\_\_\_

Treated Sill Plate: \_\_\_"X\_\_\_"  
 All Fasteners must be galvanized

Anchor Type: \_\_\_\_\_  
 Foundation Wall: Thick \_\_\_"  
 Height \_\_\_"  
 Poured \_\_\_ Block \_\_\_ Wood \_\_\_  
 Footing: \_\_\_"thick \_\_\_"wide

Sill Seal

Grade

Ceiling Height \_\_\_ "

Water Proofing/Damp Proofing:  
 Type: \_\_\_\_\_

Concrete: 3.5" Min.

Filter Material \_\_\_\_\_  
 Pea Stone

Vapor Barrier  
 Min. 4" Peastone

Drain Tile: Type: \_\_\_\_\_  
 Dia.: \_\_\_ "

Note: Footings must be 42" below Finish Grade.

